



NUMBER: 08-003-06

GROUP: Electrical

DATE: January 18, 2006

This bulletin is supplied as technical information only and is not an authorization for repair. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, or otherwise, without written permission of DaimlerChrysler Corporation.

SUBJECT:

Instrument Cluster Initialization

MODELS:

2004 - 2006 (ZH)

Crossfire Coupe/Crossfire Roadster

SPECIAL TOOLS/EQUIPMENT REQUIRED:

NPN	Battery Charger
CH7035B	General Purpose Interface Bus Cable Assembly
CH6000A	Scan Tool (DRBIII®)
CH7000A	J1962 Cable with red DRBIII® connector
CH9043	MUX Cable
CH9044	Crossfire Software Card Version 6.0 or Higher
	TechCONNECT PC

NOTE: An updated J1962 cable has been released. This cable has a red colored connector at the DRBIII® connection. Use this cable whenever a flash is being performed.

DISCUSSION:

When replacing the instrument cluster, the replacement instrument cluster must be initialized in order for the mileage to be displayed.

To initialize the cluster use the scan tool (DRBIII®) starting at the Main Menu select:

1. "System Select"
2. "Body"
3. "Instrument Cluster (IC)"
4. "Miscellaneous Functions"
5. "Module Service Replacement" - Follow the on screen instructions
6. At the "Miscellaneous Tests - Transmission Range Indicator" screen select:
 - a. "1> Active" for vehicles with an Automatic Transmission
 - b. "2> Not Active" for vehicles with a Manual Transmission

POLICY:

Information Only



Stick with the Specialists™